

 AirServer



red dot winner 2023

Redesigned for
unparalleled
performance

AirServer

Features:



Custom design with certified ports



Easy installation with magnetic mount



Single USB-C cable for power, display, network, touch and cameras



Simultaneous display of 12 sources



Enhanced connectivity with 2.5G Ethernet and commercial-grade Wi-Fi 6E RSDB



Multi-display support with up to 3x 4K60 resolution



Future-proof with BYOM ready and AirPlay 2 support



Designed and developed in Iceland

World's most powerful collaboration solution.
Can yours do 12x?

For more information, please visit www.airserver.com.



AirServer

Product specifications	AIRSERVER CONNECT 3
AirServer Base Unit dimensions	
Dimensions (HxWxD)	34 mm x 78 mm x 78 mm
Power supply	45W+ (20V, 2.25A or more) USB-C PD power adapter (optional accessory)
Power consumption	Operational: < 10W, 45W Max
General specifications	
Video input	Optional: USB to HDMI adapter
Video outputs	3x 4K UHD (3840*2160) @60Hz. HDMI 2.0a
Native protocols	AirPlay, Google Cast, Miracast
Connectivity	2.5 GbE (Gigabit Ethernet) Commercial-grade Wi-Fi 6E RSDB (up to 32 clients) This device is limited to indoor use only when operating in the 5150-5350 MHz frequency
Connections	Front: 1x USB-C 3.2 with DP alt mode 2x USB-A 3.2 Back: 1x USB-C 3.2 with DP alt mode + 45W PD 1x Ethernet LAN 2.5Gbit 1x HDMI 2.0a with CEC
Anti-theft system	Kensington lock
Certifications	FCC/CE/CB/UL/VCCI/BSMI/C-Tick/RCM/ RoHS/ETL/CSA
Touch screen support & Interactivity	Yes, over Miracast
Wireless conferencing	BYOM ready
Management and reporting	Yes
Warranty	2 years standard
DRM support	Yes (via Google Cast), including Disney+, Amazon Prime, etc
Simultaneously on screen	12 sources
Maintenance & Support	Yes (perpetual)
Software requirement	No apps or drivers required
Port certifications	USB 3.2 Gen2 (10Gb/s)/DisplayPort 1.4a (alt mode)/HDMI 2.0a